



# TECHNICAL SPECIFICATIONS

Design	Kanji - Drop - Cubik - Baobab - Berber - Coral	All other designs
Composition	100% PET (70%rPET)	
Manufacturing process	Jacquard Flatweave	
Backing composition	PES anti-slip latex	
Height	+/- 5mm 0,20"	+/- 3mm 0,12"
Weight	1650 gr/m <sup>2</sup> 49 OZ/SQY	1500 gr/m <sup>2</sup> 44 OZ/SQY
Fire resistance	flammability according to BS 4790 CFR 1630-FF1-70	flame resistance according to CAN CGSB 4.2 - 27.6
Chemical content	determination of for- maldehyde according to ISO 14184-1	prohibit azo dyes free according to EN 14362-1
Other test	thermal resistance (m <sup>2</sup> K/W) ISO 8302 from 0.032 to 0.041	thermal resistance (tog) BS 4745 from 0.32 to 0.41
	Suitable for floor heating	
Certifications	 <p>STANDARD 100 1611062 Centexbel <a href="http://www.oeko-tex.com">www.oeko-tex.com</a></p>	 <p>afaq ISO 9001 Qualité AFNOR CERTIFICATION</p>

To get your maintenance advice or get more info about our recycling program, visit our website  
[www.louisdepoortere.com](http://www.louisdepoortere.com)

